

CLIENTE/CLIENT: HISSMEKANO AB N°PEDIDO/ ORDER N°:

N°CERTIFICADO/ CERTIFICATE N°: 394/07

MATERIAL: Fe360 B - ISO 630/95

TIPO DE GUIA GUIDE TYPE	ESPECIFICACION APLICABLE APPLICABLE SPECIFICATION	ACABADO FINISHED
SUPER T50/A	Catálogo/ Catalogue Web: www.saveragroup.com Rev. 01/04	CALIBRADO/COLD-DRAWN
Gruco hongo/ Headthickness	± 0,15	Reviro / Twist 40'/m max.
Altura de guía Guide height	± 0,20	Enderezado/ Straightness f/m. 0,7 mm. max.
Paralelismo planeado Parallelism base	-	Enderezado / Straightness f/5 m. 3,5 mm. max.
Centrado de macho y hembra Symmetry of tongue and groove	± 0,10 mm.	Tolerancia macho Tolerance on tongue +0 / -0,06
Rugosidad / Roughness (Long.-Transv.)	Ra 1,6-6,3 µ	Tolerancia hembra Tolerance on groove + 0,06 / - 0

COMPOSICION QUIMICA / CHEMICAL COMPOSITION

COLADA/ CAST	C % max.	Mn % max.	P % max.	S % max.	Si % max.
Tolerancia/ Tolerance	0,17	1,40	0,045	0,045	0,40

ENSAYOS MECÁNICOS / MECHANICAL TESTS

PROBETA/ TEST	R N/mm <sup>2</sup>	E N/mm <sup>2</sup> min.	A % min	OBSERVACIONES REMARKS
Tolerancia/ Tolerance	470 - 840	355	8	

CONTROL DE CALIDAD/ QUALITY CONTROL

Sello y firma / Stamp and Signature

Vera de Bidasoa, 13/04/07

